

Amtico Entryway

Installation Guidelines

ENT-IN-20210708-05-EN

Receiving & Checking Materials

Inspect Entryway tiles prior to installation to verify type and colour. Claims cannot be accepted if tiles are installed with obvious defects. Boxes of tiles should be stored flat.

Acclimatisation of Materials

The temperature of the installation location must be stable and at a temperature of (UK) 18 – 27°C, 55% RH Tiles must be conditioned to room temperature for 24 hours prior to installation. These conditions must also be maintained during and for 48 hours after completion of installation.

Amtico Entryway matting cannot be installed externally.

Subfloor & Preparation

Dust, dirt, debris, and old adhesive residues must be removed before installation begins. Surfaces must be sound, smooth and level with all holes and cracks filled with a suitable smoothing compound.

Subfloor surfaces must be tested for moisture content and should comply with the relevant local regulations, (UK) 75% RH

Note: Moisture in excess of the recommended levels can cause the adhesive to fail. This condition can result in shifting, peaking or edge curling of the tiles.

Adhesive Selection

Entryway tiles will be fitted into the most demanding of locations. Amtico recommends a fully bonded adhesive system for the most trouble free installation.

The following adhesives are recommended for installing Entryway tiles – (UK) Amtico SF, HT Extra or PS adhesive.

Adhesive should be applied with an A2 trowel as per instructions. Roll after installation with a 45kg heavy roller to ensure good contact with the adhesive.

Installation

Install by butting edges together evenly, being careful not to compress tiles (this can cause peaked edges). Arrows are embossed or printed on the tile backing to show pile direction.

Carpet tiles will require cutting at perimeters, floor electrical outlets, and door openings. Loop pile tiles may require some trimming or clipping of tufts. This is typical of this type of construction.





If being fitted to stairs use a raised stair nosing and cut tiles to fit nosing on both step and riser, spreading adhesive to both the substrate and back of tile.

Installation methods

Modular carpet tiles from Amtico can be installed in many configurations to suit your project and design objectives.

We'll help you identify the correct installation methods for your flooring design, ensuring you get the very best in terms of finish and functionality. We recommend following our installation guidance to get the most durable and attractive results.

Please note that installation methods do not affect performance or warranties.

	 <p>Monolithic The method of layout illustrated here means that all the arrows imprinted in the carpet tile backing will be pointing in one direction. This also means that the face fibre or pile will sweep in the same direction.</p>	 <p>Quarter Turned This installation layout means the arrows on the backing will be perpendicular to each other or turned 90 degrees on every other tile.</p>	 <p>Brick In this installation layout all the arrows are installed in the same direction, but horizontal rows are offset by half the width of a tile.</p>	 <p>Random Some Amtico modular carpet styles are designed to permit a random layout, which allows installation of the carpet tile without regard for arrow direction as illustrated here.</p>
Ruffian	Yes	Yes	No	No
Recourse	Yes	Yes	Yes	Yes
Take Back	No	Yes	No	No
Force	No	No	Yes	No
Charge	No	No	Yes	No
Inertia	No	No	Yes	No